_			
assified in I	Part - Sanitized Copy Approved for Release 2013/08/05 : CIA-	-RDP80-00810A00	02500980009-1
iL.	CLASSIFICATION SECURITY INFORMATION	•	
•		DEDOO! NO	
	CENTRAL INTELLIGENCE AGENCY	REPORT NO.	
	information report	CD NO.	
			50X1-HUN
YATAUC	East Germany	DATE DISTR.	19 October 195
io ieot	Development of a Photosiece's Ibasuring	NO OF PACES	1
JBJECT	Instrument at Zeiss, Jena	NO, OF PAGES	1
	•		
LACE CQUIRED		NO. OF ENCLS	•
WCMLO			50X1-HUM
TE OF		SUPPLEMENT	τ0
FO.		REPORT NO.	
F THE UNITED ST. ND 784, OF THE TICH OF ITS COL T PROHIBITED BY	OBTAINS REPORCATION AFFECTING THE MATIGARL ORIFERISE TATES, CHITPIN FINE MEANING OF TITLE 18, SECTIONS 795 U. S. CODE, AS AUKIDED. ITS TRANSLISSION OF REVEL UTENTS TO CR DECEIFY BY ARE UNBUTHODIXED PERSON LLAU THE REPORDUCTION OF THIS FORM IS PROMISTICED.	ALUATED INFORM	IATION 50X1-HUM
1,	abteilung) (KoV) of VLB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure	mpleted the deve trument (photoe ments. The dev	elopment of lektrische ice will
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of clektrische cice will ctro- 50X1-HUM cut 1.0 cs can be
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Prob The measurement range of the instrument extends microns. Very weak photocurrents of ten rower	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of clektrische cice will ctro- 50X1-HUM cut 1.0 cs can be
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of clektrische cice will ctro- 50X1-HUM cut 1.0 cs can be
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of clektrische cice will ctro- 50X1-HUM cut 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of clektrische cice will ctro- 50X1-HUM cut 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of clektrische cice will ctro- 50X1-HUM cut 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of clektrische cice will ctro- 50X1-HUM cut 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of dektrische dice will etro- 50X1-HUM out 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of dektrische dice will etro- 50X1-HUM out 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of dektrische dice will etro- 50X1-HUM out 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of clektrische cice will ctro- 50X1-HUM cut 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of clektrische cice will ctro- 50X1-HUM cut 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of clektrische cice will ctro- 50X1-HUM cut 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of clektrische cice will ctro- 50X1-HUM cut 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of elektrische fice will etro- 50X1-HUM out 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of elektrische fice will etro- 50X1-HUM out 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of elektrische fice will etro- 50X1-HUM out 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of clektrische cice will ctro- 50X1-HUM cut 1.0 s can be using a nometer.
	abteilung) (KoV) of ViB Carl Zeiss, Jena, has co a device called a photo electric measurement ins Nesseinrichtung) for spectral absorption measure go into production in 1954. It consists of a si meter, a photocell and a sample holder (Frob The measurement range of the instrument extends microns. Very weak photocurrents of ten power measured. The range can be extended into the in	mpleted the deve trument (photos ments. The dev ngle-thread ele ewechsler). from 0.25 to ab minus 14 ampere fra-red band by	elopment of elektrische fice will etro- 50X1-HUM out 1.0 s can be using a nometer.

	U	L4331F:GATIO	N: SEARET	
STATE 3	YVVK Z	X NSRB	DISTRIBUTION	OST Ev x
ARMY 17	X AIR	x Fai		

50X1-HUM

